

TOSOT



THERMOPOMPES

HEAT PUMPS



LOMO 23



TOSOTAMERICA.COM

TOSOTFR19L23

LOMO 23

THERMOPOMPES LOMO23 À SIMPLE ZONE
INVERTER SEER 23-20
 9 000 BTU À 36 000 BTU

SINGLE-ZONE LOMO23 HEAT PUMPS
23-20 SEER INVERTER
 9,000 BTU TO 36,000 BTU



- Affichage à DEL
- Chauffage à -25° C / -13° F
- Climatisation en basse température : -15° C / 5° F
- Thermostat mural en option
- Aussi disponible en configuration multi-zones
- Rabais disponibles
- LED display
- Heating down to -25° C / -13° F
- Low ambient cooling at -15° C / 5° F
- Optional wall thermostat
- Also available in Multi-Zone
- Rebates available with almost every utility company in North America

	TW09HQ2C2D	TW12HQ2C2D	TW18HQ2C2D	TW24HQ2C2D	TW30HQ2C2D	TW36HQ2C2D
Alimentation / Power Supply	208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph	208-230V, 60Hz, 1Ph
Courant nominal refroidissement <i>Rated Current Cooling</i>	A	5.8	6.0	10.4	14.5	17.0
Courant nominal chauffage <i>Rated Current Heating</i>	A	6.0	6.3	12.6	14.5	17.5
RENDEMENT DU SYSTÈME / SYSTEM PERFORMANCE						
Déshumidification / Dehumidification	l/h	0.8	1.4	1.8	2.0	3.0
Puissance frigorifique / Cooling Capacity	BTU/h	9,000 (3,100 - 9,800)	12,000 (3,100 - 13,000)	18,000 (6,800 - 20,000)	22,000 (8,820 - 27,000)	28,000 (9,490 - 30,030)
Puissance calorifique / Heating Capacity	BTU/h	11,000 (1,911 - 12,000)	13,000 (2,400 - 14,000)	19,800 (7,340 - 23,500)	23,000 (8,820 - 30,710)	28,400 (10,000 - 32,990)
SEER/EER		23 / 14.29	22 / 12.50	20 / 12.50	20 / 12.50	18 / 10.40
HSPF/COP		10.5 / 3.16	11.0 / 3.46	10.0 / 3.35	10 / 3.37	9 / 3.0
APPAREIL INTÉRIEUR / INDOOR UNIT						
Débit d'air (B/H) / Airflow (L/H)	PCM / CFM	171 / 377	171 / 400	335 / 559	530 / 706	412 / 706
Niveau de pression acoustique (B/H) <i>Sound Pressure Level (L/H)</i>	dB(A)	29 / 43	29 / 45	39 / 47	36 / 48	37 / 51
Dimensions (LxHxP) / Unit Dim. (WxHxD)	po. / in.	33.4 x 11.4 x 8.2	33.4 x 11.4 x 8.2	38.2 x 11.8 x 8.8	42.4 x 12.8 x 9.7	53.1 x 12.8 x 10
Poids net/brut / Net/Gross Weight	lb	22.1 / 26.5	22.1 / 26.5	27.6 / 34.2	34.2 / 41.9	41.9 / 51.8
APPAREIL EXTÉRIEUR / OUTDOOR UNIT						
Type de compresseur / Compressor Type	BALANCEMENT <i>SWING</i>	BALANCEMENT <i>SWING</i>	ROTATIF / ROTARY	ROTATIF / ROTARY	ROTATIF / ROTARY	ROTATIF / ROTARY
Niveau sonore / Sound Pressure Level	dB(A)	53	54	55	59	62
Dimensions (LxHxP) / Unit Dim. (WxHxD)	po. / in.	33.4 x 21.3 x 12.6	33.4 x 23.6 x 12.6	37.6 x 27.6 x 12.6	38.6 x 31.1 x 16.8	38.6 x 31.1 x 16.8
Poids net/brut / Net/Gross Weight	lb	78 / 84	86 / 93	105 / 115	142 / 153	154 / 165
Réfrigérant/Charge / Refrigerant/Charge	oz.	R410A / 45.9	R410A / 47.6	R410A / 56.4	R410A / 77.6	R410A / 84.6
Grosseur du conduit (liquide - gaz) <i>Line Set Size (Liquid - Gas)</i>	po. / in.	1/4" - 3/8"	1/4" - 1/2"	1/4" - 5/8"	1/4" - 5/8"	1/4" - 5/8"
Longueur max. du tuyau / Max. Pipe Length	pi. / ft.	49.2	65.6	82	82	98.4
Élévation maximale / Max. Elevation	pi. / ft.	49	49	49	49	49
MCA	A	9	9	16	20	24
MOP	A	15	15	25	30	40
Calibre du fil/nombre de fils / Wire Size/# Wires		14 AWG*4 torsadé, dénudé / 14 AWG*4 Stranded, unshielded				

MODULE Wi-Fi DISPONIBLE
Wi-Fi MODULE AVAILABLE

TL127000600_L72279



THERMOSTAT
 (Facultatif / Optional)

XE71